



Studio 100

Design	5 driver, 3-way floorstanding
Crossover	3rd-order electro-acoustic at 2.0 kHz, 3rd-order electro-acoustic at 300 Hz (bass drivers)
High-Frequency Driver	25-mm (1 in) G-PAL™ dome, die-cast heatsink chassis, ferro-fluid cooled, IMS / SHOCK-MOUNT™
Midrange Driver(s)	178-mm (7 in) S-PAL™ cone, 38-mm (1-1/2 in) voice coil, AVS™ die-cast heatsink chassis, IMS / SHOCK-MOUNT™
Bass Driver	Three 178-mm (7 in) mineral-filled polypropylene cones, 38-mm (1-1/2 in) voice coils, AVS™ die-cast heatsink chassis, IMS / SHOCK-MOUNT™
Low Frequency Extension	25 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 44 Hz - 22 kHz
30° Off-Axis	±2 dB from 44 Hz - 20 kHz
Sensitivity - Room / Anechoic	93 dB / 90 dB
Suitable Amplifier Power Range	15 - 350 watts
Maximum Input Power	230 watts
Impedance	Compatible with 8 ohms
Height, Width, Depth (Height includes spikes or outrigger feet)	112 cm x 24.1 cm x 43.1 cm 44-1/8 in x 9-1/2 in x 16-15/16 in

Weight	35.4 kg / 78 lb each
Finishes	Cherry, Rosenut, Black